

CROWN



S E R I E S



CLASS IV | CUSHION

C A P A C I T Y S H E E T

Page	Title
3	General Information
3	Derate with Trucks Longer than 42"
4	Truck Capacity with Forks Only
5	Truck Capacity with Sideshifter
6	Truck Capacity with Fork Positioner
7	Truck Capacity with Push/Pull
8	Truck Capacity with Carton Clamp
9	Approved Attachments
10	Extended Load Center Capacities

General Information

- Length and heights are in inches and capacity in pounds.
- Unless otherwise specified, capacities are for trucks equipped with standard mast tilts and standard tread widths.
- Capacities for trucks with attachments are valid only for Crown approved attachments as listed on Master Index.
- See D-628 section 4 for capacity plate information.
- How to use these charts to determine capacities.
 - Determine basic capacity from charts on pages 4 thru 8.
 - Apply additional derate if truck is equipped with forks longer than 42" on page 3.
 - Determine extended load center capacity, if necessary, on page 10.

Exp: C5 1000-50 1. 4650 lb to 188" at 24" LC
 Cushion Tire
 188" TT 2. 4650 - 150 = 4500 to 188" at 24" LC
 Narrow Tread
 Sideshifter 3. 4500 ⇒ 3600 lb to 188" at 30" LC
 60" x 1.75" x 5" Forks

Derate with Forks Longer than 42"

Capacity Derate at 24" Load Center
 For Optional Fork Sizes and Lengths

Fork Length	C5 1000-40 and -50		C5 1000-60 and -65
	1.75 x 4.00	1.75 x 5.00	1.75 x 5.00
42	0	50	0
43.31	0	50	0
45	50	50	50
48	50	100	50
54	100	150	100
60	100	150	150



Forks Only and Wide Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40	C5 1000-50	Lift Height	C5 1000-60	Lift Height	C5 1000-65
			Cushion Tire	Cushion Tire		Cushion Tire		Cushion Tire
TL	All	81	4000	5000	81	6000	81	6500
		122	4000	5000	114	6000	112	6500
		126	4000	5000	118	6000	124	6500
		138	4000	5000	130	6000	136	6500
		150	4000	5000	142	6000	142	n/a
TT	83" thru 95"	150	4000	5000	155	6000	150	6500
		182	4000	5000	174	6000	171	6400
		188	4000	4950	180	6000	189	5300
		206	3600	4550	198	4650	199	4650
		216	3500	4450	208	4300	208	n/a
	101" thru 113"	170	4000	5000	175	6000	175	6000
		188	4000	4950	200	5650	214	5350
		231	3500	4450	223	5150	229	4950
		246	3250	4100	238	4750	241	4550
		258	3200	4000	250	4000	250	n/a
	119" thru 125"	170	4000	5000	155	n/a	155	n/a
		188	4000	4950	188	n/a	188	n/a
		231	3500	4450	223	n/a	223	n/a
		276	2600	3250	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	4500	188	n/a	188	n/a
		210	n/a	4500	216	n/a	216	n/a
		240	n/a	4250	240	n/a	240	n/a
		258	n/a	3950	258	n/a	258	n/a
		276	n/a	3250	276	n/a	276	n/a
	101" thru 107"	188	n/a	4500	188	n/a	188	n/a
		240	n/a	4250	240	n/a	240	n/a
		294	n/a	2300	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Forks Only and Narrow Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40	C5 1000-50	Lift Height	C5 1000-60	Lift Height	C5 1000-65
			Cushion Tire	Cushion Tire		Cushion Tire		Cushion Tire
TL	All	81	4000	5000	81	6000	81	6500
		122	4000	5000	114	6000	112	6500
		126	4000	5000	118	6000	124	6500
		138	4000	5000	130	6000	136	6500
		150	4000	5000	142	6000	142	n/a
TT	83" thru 95"	150	4000	5000	155	6000	150	6500
		182	4000	5000	174	6000	171	6400
		188	4000	4950	180	6000	189	5300
		206	3600	4550	198	4650	199	4650
		216	3500	4450	208	4300	208	n/a
	101" thru 113"	170	4000	5000	175	6000	175	6000
		188	4000	4950	200	5650	214	5200
		231	3500	4450	223	4950	229	4550
		246	3250	4100	238	4000	241	3800
		258	3200	4000	250	3250	250	n/a
	119" thru 125"	170	4000	5000	155	n/a	155	n/a
		188	4000	4950	188	n/a	188	n/a
		231	3500	4450	223	n/a	223	n/a
		276	2600	2500	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	4500	188	n/a	188	n/a
		210	n/a	4500	216	n/a	216	n/a
		240	n/a	3950	240	n/a	240	n/a
		258	n/a	3450	258	n/a	258	n/a
		276	n/a	2950	276	n/a	276	n/a
	101" thru 107"	188	n/a	4500	188	n/a	188	n/a
		240	n/a	4200	240	n/a	240	n/a
		294	n/a	1900	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Sideshifter and Wide Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40 Cushion Tire	C5 1000-50 Cushion Tire	Lift Height	C5 1000-60 Cushion Tire	Lift Height	C5 1000-65 Cushion Tire
TL	All	81	3700	4650	81	5600	81	6050
		122	3700	4650	114	5600	112	6050
		126	3700	4650	118	5600	124	6050
		138	3700	4650	130	5600	136	6050
		150	3700	4650	142	5600	142	n/a
TT	83" thru 95"	150	3700	4650	155	5600	150	6050
		182	3700	4650	174	5600	171	6000
		188	3700	4650	180	5600	189	4950
		206	3350	4250	198	4300	199	4300
		216	3250	4150	208	4000	208	n/a
	101" thru 113"	170	3700	4650	175	5600	175	5600
		188	3700	4650	200	5250	214	5000
		231	3250	4150	223	4800	229	4600
		246	3000	3800	238	4400	241	4250
		258	2950	3750	250	3700	250	n/a
	119" thru 125"	170	3700	4650	155	n/a	155	n/a
		188	3700	4650	188	n/a	188	n/a
		231	3250	4150	223	n/a	223	n/a
		276	2400	3000	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	4200	188	n/a	188	n/a
		210	n/a	4200	216	n/a	216	n/a
		240	n/a	3950	240	n/a	240	n/a
		258	n/a	3700	258	n/a	258	n/a
		276	n/a	3000	276	n/a	276	n/a
	101" thru 107"	188	n/a	4200	188	n/a	188	n/a
		240	n/a	3950	240	n/a	240	n/a
		294	n/a	2100	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Sideshifter and Narrow Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40 Cushion Tire	C5 1000-50 Cushion Tire	Lift Height	C5 1000-60 Cushion Tire	Lift Height	C5 1000-65 Cushion Tire
TL	All	81	3700	4650	81	5600	81	6050
		122	3700	4650	114	5600	112	6050
		126	3700	4650	118	5600	124	6050
		138	3700	4650	130	5600	136	6050
		150	3700	4650	142	5600	142	n/a
TT	83" thru 95"	150	3700	4650	155	5600	150	6050
		182	3700	4650	174	5600	171	6000
		188	3700	4650	180	5600	189	4950
		206	3350	4250	198	4300	199	4300
		216	3250	4150	208	4000	208	n/a
	101" thru 113"	170	3700	4650	175	5600	175	5600
		188	3700	4650	200	5250	214	4850
		231	3250	4150	223	4600	229	4200
		246	3000	3800	238	3700	241	3500
		258	2950	3750	250	3000	250	n/a
	119" thru 125"	170	3700	4650	155	n/a	155	n/a
		188	3700	4650	188	n/a	188	n/a
		231	3250	4150	223	n/a	223	n/a
		276	2400	2300	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	4200	188	n/a	188	n/a
		210	n/a	4200	216	n/a	216	n/a
		240	n/a	3700	240	n/a	240	n/a
		258	n/a	3200	258	n/a	258	n/a
		276	n/a	2750	276	n/a	276	n/a
	101" thru 107"	188	n/a	4200	188	n/a	188	n/a
		240	n/a	3900	240	n/a	240	n/a
		294	n/a	1700	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a



Fork Positioner and Wide Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40	C5 1000-50	Lift Height	C5 1000-60	Lift Height	C5 1000-65
			Cushion Tire	Cushion Tire		Cushion Tire		Cushion Tire
TL	All	81	3550	4500	81	5250	81	5700
		122	3550	4500	114	5250	112	5700
		126	3550	4500	118	5250	124	5700
		138	3550	4500	130	5250	136	5700
		150	3550	4500	142	5250	142	n/a
TT	83" thru 95"	150	3550	4500	155	5250	150	5700
		182	3550	4500	174	5250	171	5650
		188	3550	4450	180	5250	189	4600
		206	3200	4100	198	4000	199	4000
		216	3100	4000	208	3700	208	n/a
	101" thru 113"	170	3550	4500	175	5250	175	5250
		188	3550	4450	200	4950	214	4650
		231	3100	4000	223	4450	229	4300
		246	2850	3650	238	4100	241	3900
		258	2800	3550	250	3400	250	n/a
	119" thru 125"	170	3550	4500	155	n/a	155	n/a
		188	3550	4450	188	n/a	188	n/a
		231	3100	4000	223	n/a	223	n/a
		276	2250	2850	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	4050	188	n/a	188	n/a
		210	n/a	4050	216	n/a	216	n/a
		240	n/a	3800	240	n/a	240	n/a
		258	n/a	3550	258	n/a	258	n/a
		276	n/a	2850	276	n/a	276	n/a
	101" thru 107"	188	n/a	4050	188	n/a	188	n/a
		240	n/a	3800	240	n/a	240	n/a
		294	n/a	1950	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Fork Positioner and Narrow Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40	C5 1000-50	Lift Height	C5 1000-60	Lift Height	C5 1000-65
			Cushion Tire	Cushion Tire		Cushion Tire		Cushion Tire
TL	All	81	3550	4500	81	5250	81	5700
		122	3550	4500	114	5250	112	5700
		126	3550	4500	118	5250	124	5700
		138	3550	4500	130	5250	136	5700
		150	3550	4500	142	5250	142	n/a
TT	83" thru 95"	150	3550	4500	155	5250	150	5700
		182	3550	4500	174	5250	171	5650
		188	3550	4450	180	5250	189	4600
		206	3200	4100	198	4000	199	4000
		216	3100	4000	208	3700	208	n/a
	101" thru 113"	170	3550	4500	175	5250	175	5250
		188	3550	4450	200	4950	214	4500
		231	3100	4000	223	4300	229	3900
		246	2850	3650	238	3400	241	3200
		258	2800	3550	250	2700	250	n/a
	119" thru 125"	170	3550	4500	155	n/a	155	n/a
		188	3550	4450	188	n/a	188	n/a
		231	3100	4000	223	n/a	223	n/a
		276	2250	2150	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	4050	188	n/a	188	n/a
		210	n/a	4050	216	n/a	216	n/a
		240	n/a	3500	240	n/a	240	n/a
		258	n/a	3050	258	n/a	258	n/a
		276	n/a	2600	276	n/a	276	n/a
	101" thru 107"	188	n/a	4050	188	n/a	188	n/a
		240	n/a	3750	240	n/a	240	n/a
		294	n/a	1600	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Push/Pull and Wide Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40 Cushion Tire	C5 1000-50 Cushion Tire	Lift Height	C5 1000-60 Cushion Tire	Lift Height	C5 1000-65 Cushion Tire
TL	All	81	3150	4050	81	n/a	81	n/a
		122	3150	4050	114	n/a	112	n/a
		126	3150	4050	118	n/a	124	n/a
		138	3150	4050	130	n/a	136	n/a
		150	3150	4050	142	n/a	142	n/a
TT	83" thru 95"	150	3150	4050	155	n/a	150	n/a
		182	3150	4050	174	n/a	171	n/a
		188	3150	4000	180	n/a	189	n/a
		206	2800	3600	198	n/a	199	n/a
		216	2700	3550	208	n/a	208	n/a
	101" thru 113"	170	3150	4050	175	n/a	175	n/a
		188	3150	4000	200	n/a	214	n/a
		231	2700	3550	223	n/a	229	n/a
		246	2450	3200	238	n/a	241	n/a
		258	2400	3150	250	n/a	250	n/a
	119" thru 125"	170	3150	4050	155	n/a	155	n/a
		188	3150	4000	188	n/a	188	n/a
		231	2700	3550	223	n/a	223	n/a
		276	1850	2450	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	3400	188	n/a	188	n/a
		210	n/a	3400	216	n/a	216	n/a
		240	n/a	3350	240	n/a	240	n/a
		258	n/a	3100	258	n/a	258	n/a
		276	n/a	2450	276	n/a	276	n/a
	101" thru 107"	188	n/a	3400	188	n/a	188	n/a
		240	n/a	3350	240	n/a	240	n/a
		294	n/a	1550	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Push/Pull and Narrow Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40 Cushion Tire	C5 1000-50 Cushion Tire	Lift Height	C5 1000-60 Cushion Tire	Lift Height	C5 1000-65 Cushion Tire
TL	All	81	3150	4050	81	n/a	81	n/a
		122	3150	4050	114	n/a	112	n/a
		126	3150	4050	118	n/a	124	n/a
		138	3150	4050	130	n/a	136	n/a
		150	3150	4050	142	n/a	142	n/a
TT	83" thru 95"	150	3150	4050	155	n/a	150	n/a
		182	3150	4050	174	n/a	171	n/a
		188	3150	4000	180	n/a	189	n/a
		206	2800	3600	198	n/a	199	n/a
		216	2700	3550	208	n/a	208	n/a
	101" thru 113"	170	3150	4050	175	n/a	175	n/a
		188	3150	4000	200	n/a	214	n/a
		231	2700	3550	223	n/a	229	n/a
		246	2450	3200	238	n/a	241	n/a
		258	2400	3150	250	n/a	250	n/a
	119" thru 125"	170	3150	4050	155	n/a	155	n/a
		188	3150	4000	188	n/a	188	n/a
		231	2700	3550	223	n/a	223	n/a
		276	1850	1750	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	3400	188	n/a	188	n/a
		210	n/a	3400	216	n/a	216	n/a
		240	n/a	3100	240	n/a	240	n/a
		258	n/a	2600	258	n/a	258	n/a
		276	n/a	2150	276	n/a	276	n/a
	101" thru 107"	188	n/a	3400	188	n/a	188	n/a
		240	n/a	3300	240	n/a	240	n/a
		294	n/a	1200	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a



Carton Clamp and Wide Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40 Cushion Tire	C5 1000-50 Cushion Tire	Lift Height	C5 1000-60 Cushion Tire	Lift Height	C5 1000-65 Cushion Tire
TL	All	81	2650	3500	81	n/a	81	n/a
		122	2650	3500	114	n/a	112	n/a
		126	2650	3500	118	n/a	124	n/a
		138	2650	3500	130	n/a	136	n/a
		150	2650	3500	142	n/a	142	n/a
TT	83" thru 95"	150	2650	3500	155	n/a	150	n/a
		182	2650	3500	174	n/a	171	n/a
		188	2650	3500	180	n/a	189	n/a
		206	2250	3150	198	n/a	199	n/a
		216	2200	3050	208	n/a	208	n/a
	101" thru 113"	170	2650	3500	175	n/a	175	n/a
		188	2650	3500	200	n/a	214	n/a
		231	2200	3050	223	n/a	229	n/a
		246	1950	2750	238	n/a	241	n/a
		258	1900	2650	250	n/a	250	n/a
	119" thru 125"	170	2650	3500	155	n/a	155	n/a
		188	2650	3500	188	n/a	188	n/a
		231	2200	3050	223	n/a	223	n/a
		276	1350	1950	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	2900	188	n/a	188	n/a
		210	n/a	2900	216	n/a	216	n/a
		240	n/a	2900	240	n/a	240	n/a
		258	n/a	2600	258	n/a	258	n/a
		276	n/a	1950	276	n/a	276	n/a
	101" thru 107"	188	n/a	2900	188	n/a	188	n/a
		240	n/a	2900	240	n/a	240	n/a
		294	n/a	1050	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

Carton Clamp and Narrow Tread Axle

Truck Capacity at 24" Load Center

Mast Type	Collapsed Height	Lift Height	C5 1000-40 Cushion Tire	C5 1000-50 Cushion Tire	Lift Height	C5 1000-60 Cushion Tire	Lift Height	C5 1000-65 Cushion Tire
TL	All	81	2650	3500	81	n/a	81	n/a
		122	2650	3500	114	n/a	112	n/a
		126	2650	3500	118	n/a	124	n/a
		138	2650	3500	130	n/a	136	n/a
		150	2650	3500	142	n/a	142	n/a
TT	83" thru 95"	150	2650	3500	155	n/a	150	n/a
		182	2650	3500	174	n/a	171	n/a
		188	2650	3500	180	n/a	189	n/a
		206	2250	3150	198	n/a	199	n/a
		216	2200	3050	208	n/a	208	n/a
	101" thru 113"	170	2650	3500	175	n/a	175	n/a
		188	2650	3500	200	n/a	214	n/a
		231	2200	3050	223	n/a	229	n/a
		246	1950	2750	238	n/a	241	n/a
		258	1900	2650	250	n/a	250	n/a
	119" thru 125"	170	2650	3500	155	n/a	155	n/a
		188	2650	3500	188	n/a	188	n/a
		231	2200	3050	223	n/a	223	n/a
		276	1350	1250	268	n/a	268	n/a
		291	n/a	n/a	283	n/a	283	n/a
QUAD	83" thru 95"	188	n/a	2900	188	n/a	188	n/a
		210	n/a	2900	216	n/a	216	n/a
		240	n/a	2600	240	n/a	240	n/a
		258	n/a	2150	258	n/a	258	n/a
		276	n/a	1650	276	n/a	276	n/a
	101" thru 107"	188	n/a	2900	188	n/a	188	n/a
		240	n/a	2850	240	n/a	240	n/a
		294	n/a	650	294	n/a	294	n/a
		312	n/a	n/a	312	n/a	312	n/a

C-5 Series

Capacity Sheet

Approved Sideshifters

Truck Model	Carriage Width	Attachment Mfg.	Mfg. PN	Crown PN
C5 1000-40	38"	Cascade	55F-SSS-A060	136579-002
C5 1000-40	44"	Cascade	55F-SSS-A058	136579-003
C5 1000-50	38"	Cascade	55F-SSS-A060	136579-002
C5 1000-50	44"	Cascade	55F-SSS-A058	136579-003
C5 1000-60	38"	Cascade	65F-SSS-B059	136579-004
C5 1000-60	44"	Cascade	65F-SSS-B060	136579-005
C5 1000-65	38"	Cascade	65F-SSS-B059	136579-004
C5 1000-65	44"	Cascade	65F-SSS-B060	136579-005

Approved Fork Positioners

Truck Model	Carriage Width	Attachment Mfg.	Mfg. PN	Crown PN
C5 1000-40	38"	Cascade	55F-FPS-A041	129710-002
C5 1000-40	44"	Cascade	55F-FPS-A049	129710-003
C5 1000-50	38"	Cascade	55F-FPS-A041	129710-002
C5 1000-50	44"	Cascade	55F-FPS-A049	129710-003
C5 1000-60	38"	Cascade	100F-FPS-B041	129710-004
C5 1000-60	44"	Cascade	100F-FPS-B049	129710-005
C5 1000-65	38"	Cascade	100F-FPS-B041	129710-004
C5 1000-65	44"	Cascade	100F-FPS-B049	129710-005

Approved Push/Pulls

Truck Model	Carriage Width	Attachment Mfg.	Mfg. PN	Crown PN
C5 1000-40	38"	Cascade	35E-PPB-A003	112718-001
C5 1000-40	38"	Cascade	35E-PPS-A003	112718-002
C5 1000-40	38"	Cascade	35E-QPB-Q002	113003-001
C5 1000-40	44"	Cascade	35E-PPB-A003	112718-001
C5 1000-40	44"	Cascade	35E-PPS-A003	112718-002
C5 1000-40	44"	Cascade	35E-QPB-Q002	113003-001
C5 1000-50	38"	Cascade	45E-PPB-A003	112718-003
C5 1000-50	38"	Cascade	45E-PPS-A003	112718-004
C5 1000-50	38"	Cascade	45E-QPB-Q002	113003-002
C5 1000-50	44"	Cascade	45E-PPB-A003	112718-003
C5 1000-50	44"	Cascade	45E-PPS-A003	112718-004
C5 1000-50	44"	Cascade	45E-QPB-Q002	113003-002

Approved Carton Clamps*

Truck Model	Carriage Width	Attachment Mfg.	Mfg. PN	Crown PN
C5 1000-40	38"	Cascade	35D-CCS-35A	112721-001
C5 1000-40	44"	Cascade	35D-CCS-35A	112721-001
C5 1000-50	38"	Cascade	35D-CCS-35A	112721-001
C5 1000-50	44"	Cascade	35D-CCS-35A	112721-001

*Capacities only valid for non-sideshifting carton clamps. If s/s is desired, then EA is required.



Extended Load Center Capacities

Capacity at 24" Load Center	Extended Load Center Capacity			
	27" LC	30" LC	33" LC	36" LC
6000	5300	4800	4350	4000
5950	5250	4750	4300	3950
5900	5200	4700	4250	3900
5850	5200	4650	4250	3900
5800	5150	4600	4200	3850
5750	5100	4600	4150	3800
5700	5050	4550	4100	3800
5650	5000	4500	4100	3750
5600	4950	4450	4050	3700
5550	4900	4400	4000	3700
5500	4850	4400	4000	3650
5450	4800	4350	3950	3600
5400	4800	4300	3900	3600
5350	4750	4250	3850	3550
5300	4700	4200	3850	3500
5250	4650	4200	3800	3500
5200	4600	4150	3750	3450
5150	4550	4100	3700	3400
5100	4500	4050	3700	3400
5050	4450	4000	3650	3350
5000	4400	4000	3600	3300
4950	4400	3950	3600	3300
4900	4350	3900	3550	3250
4850	4300	3850	3500	3200
4800	4250	3800	3450	3200
4750	4200	3800	3450	3150
4700	4150	3750	3400	3100
4650	4100	3700	3350	3100
4600	4050	3650	3300	3050
4550	4000	3600	3300	3000
4500	4000	3600	3250	3000
4450	3950	3550	3200	2950
4400	3900	3500	3200	2900
4350	3850	3450	3150	2900
4300	3800	3400	3100	2850
4250	3750	3400	3050	2800
4200	3700	3350	3050	2800
4150	3650	3300	3000	2750
4100	3600	3250	2950	2700
4050	3600	3200	2900	2700
4000	3550	3200	2900	2650
3950	3500	3150	2850	2600
3900	3450	3100	2800	2600
3850	3400	3050	2800	2550
3800	3350	3000	2750	2500

Capacity at 24" Load Center	Extended Load Center Capacity			
	27" LC	30" LC	33" LC	36" LC
3750	3300	3000	2700	2500
3700	3250	2950	2650	2450
3650	3200	2900	2650	2400
3600	3200	2850	2600	2400
3550	3150	2800	2550	2350
3500	3100	2800	2500	2300
3450	3050	2750	2500	2300
3400	3000	2700	2450	2250
3350	2950	2650	2400	2200
3300	2900	2600	2400	2200
3250	2850	2600	2350	2150
3200	2800	2550	2300	2100
3150	2800	2500	2250	2100
3100	2750	2450	2250	2050
3050	2700	2400	2200	2000
3000	2650	2400	2150	2000
2950	2600	2350	2100	1950
2900	2550	2300	2100	1900
2850	2500	2250	2050	1900
2800	2450	2200	2000	1850
2750	2400	2200	2000	1800
2700	2400	2150	1950	1800
2650	2350	2100	1900	1750
2600	2300	2050	1850	1700
2550	2250	2000	1850	1700
2500	2200	2000	1800	1650
2450	2150	1950	1750	1600
2400	2100	1900	1700	1600
2350	2050	1850	1700	1550
2300	2000	1800	1650	1500
2250	2000	1800	1600	1500
2200	1950	1750	1600	1450
2150	1900	1700	1550	1400
2100	1850	1650	1500	1400
2050	1800	1600	1450	1350
2000	1750	1600	1450	1300
1950	1700	1550	1400	1300
1900	1650	1500	1350	1250
1850	1600	1450	1300	1200
1800	1600	1400	1300	1200
1750	1550	1400	1250	1150
1700	1500	1350	1200	1100
1650	1450	1300	1200	1100
1600	1400	1250	1150	1050
1550	1350	1200	1100	1000
1500	1300	1200	1050	1000



Crown Equipment Corporation
New Bremen, Ohio 45869 USA
Tel 419-629-2311
Fax 419-629-3796
crown.com

You can count on Crown to build lift trucks designed for safe operation, but that's only part of the safety equation. Crown encourages safe operating practices through ongoing operator training, safety-focused supervision, maintenance and a safe working environment. Go to crown.com and view our safety section to learn more.

Because Crown is continually improving its products, specifications are subject to change without notice.

Crown, the Crown logo, the color beige, the Momentum mark, Access 1 2 3, InfoLink, Work Assist, FlexSeat, Intrinsic Stability System and eSmart are trademarks of Crown Equipment Corporation. Other trademarks are owned by their manufacturers.

Copyright 2009 Crown Equipment Corporation
SF18360 10/09
Printed in U.S.A.